



49 CFR 192.473 External Corrosion Control: Interference Currents

(a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
 (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date	Location Map Attached <input type="checkbox"/> YES <input type="checkbox"/> NO	Case Number
------	---	-------------

General Data

Company	Contact	
Address	Office Phone	Cell Phone
Rectifier/Ground Bed Location		
County	Tax District	
Nearest Town or Municipality	Property Owner	

Rectifier Data

Rectifier Designation / Description		
Rated Output	Operating Output	Date Output Taken
DC Volts	DC Volts	
DC Amps	DC Amps	

Ground Bed Description

Location From Rectifier			
Feet	<input type="checkbox"/> North	<input type="checkbox"/> Northeast	<input type="checkbox"/> East
	<input type="checkbox"/> Southeast	<input type="checkbox"/> South	<input type="checkbox"/> Southwest
	<input type="checkbox"/> West	<input type="checkbox"/> Northwest	
Type of Ground Bed	Number of Anodes	Type of Anodes	Anode Spacing
Conventional		Graphite	Feet

Structure Protected

Type of Structure	Size	Length
Coating Type	Remarks	

Other Structures

Companies that may be Affected		