



49 CFR 192.473 External Corrosion Control: Interference Currents
 (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
 (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 3/28/2012	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 1203112
--------------------------	--	-------------------------------

General Data

Company PDC MOUNTAINWORK	Contact Rob Beam / Hal George	
Address 120 GENESIS BLVD. BRIDGEPORT WV 26330	Office Phone 304-842-3597	Cell Phone

Rectifier/Ground Bed Location OFF WENDALL ROAD AT THE PDC COMET RECTIFIER SITE N 39.30583 W 80.10719
--

County TAYLOR	Tax District
Nearest Town or Municipality GRATON	Property Owner

Rectifier Data

Rectifier Designation / Description COMET STATION		
Rated Output 40 DC Volts	Operating Output 3.61 DC Volts	Date Output Taken 3/29/2012
20 DC Amps	1.75 DC Amps	

Ground Bed Description

Location From Rectifier @ Rectifier	Feet	<input type="checkbox"/> North <input type="checkbox"/> Northeast <input type="checkbox"/> East <input type="checkbox"/> Southeast <input type="checkbox"/> South <input type="checkbox"/> Southwest <input type="checkbox"/> West <input type="checkbox"/> Northwest
Type of Ground Bed DEEP WELL	Number of Anodes 12	Type of Anodes MMO
		Anode Spacing 300' WELL 15' Feet

Structure Protected

Type of Structure P. Pipeline	Size 3" x 12"	Length
Coating Type FBE	Remarks	

Other Structures

Companies that may be Affected EQT	DOMINION