

		49 CFR 192.473 External Corrosion Control: Interference Currents (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents. (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.	
Rectifier Directory			
Date 3-7-2013	Location Map Attached ☐ YES ☒ NO		Case Number 1303100
General Data			
Company PDC ENERGY		Contact ROB BEAM	
Address 120 GENESIS BLVD. BRIDGEPORT, WV 26330		Office Phone 304-808-6249	Cell Phone 304-629-9071
Rectifier/Ground Bed Location BOE Rectifier - BOE COMPRESSOR SITE OFF MT. CLARE ROAD			
County HARRISON		Tax District	
Nearest Town or Municipality CLARKSBURG, WV		Property Owner	
Rectifier Data			
Rectifier Designation / Description BOE COMPRESSOR UNIVERSAL RECTIFIER			
Rated Output 40 DC Volts		Operating Output 1.56 DC Volts	
20 DC Amps		1.24 DC Amps	
Date Output Taken			
Ground Bed Description			
Location From Rectifier @ Rectifier Feet ☐ North ☐ Northeast ☐ East ☐ Southeast ☐ South ☐ Southwest ☐ West ☐ Northwest			
Type of Ground Bed DEEP WELL Conventional	Number of Anodes 10	Type of Anodes MIXED METAL OXIDE Graphite	Anode Spacing 100-300' DEEP Feet
Structure Protected			
Type of Structure STEEL PIPELINE (COATED)		Size 6", 10", 12"	Length
Coating Type FBE	Remarks		
Other Structures			
Companies that may be Affected DOMINION		EQT	