



49 CFR 192.473 External Corrosion Control: Interference Currents

(a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.

(b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date <i>2-13-12</i>	Location Map Attached ☒ YES ☐ NO	Case Number 1202111
------------------------	--	------------------------

General Data

Company <i>DOMINION TRANSMISSION WESTON G&P</i>	Contact <i>WALLACE D. FORESTER</i>
Address <i>1333 VALLEY CHAPEL RD. WESTON G&P WESTON WVA 26452</i>	Office Phone <i>304-269-3174</i>
	Cell Phone <i>304-625-1365</i>

Rectifier/Ground Bed Location

*700 FT EAST OF JCT OF RT 57 & 5 1/4 . RECTON
BANK NORTH OF LINE KING OF RT 57*

County <i>BARBOR CO</i>	Tax District <i>WEST</i>
Nearest Town or Municipality <i>PHILIPPI</i>	Property Owner <i>CHUCK PIERCY</i>

Rectifier Data

Rectifier Designation / Description

UNIVERSAL MODEL ASA I 40-20

Rated Output <i>40</i> DC Volts	Operating Output <i>5.0</i> DC Volts	Date Output Taken <i>1-20-12</i>
<i>20</i> DC Amps	<i>0.335</i> DC Amps	

Ground Bed Description

Location From Rectifier <i>700</i> Feet	☐ North ☐ Northeast ☐ East ☐ Southeast ☐ South ☐ Southwest ☒ West ☐ Northwest						
Type of Ground Bed <i>CONVENTIONAL</i>	Number of Anodes <i>10</i>	Type of Anodes <i>MIX METAL OXIDE</i>	Anode Spacing <i>15</i> Feet				

Structure Protected

Type of Structure <i>GAS LINE</i>	Size <i>6"</i>	Length <i>9,000</i>
Coating Type <i>FBE</i>	Remarks	

Other Structures

Companies that may be Affected <i>CONSOLID / C&N</i>	<i>ENERVEST</i>
<i>PETROLEUM DEVELOPMENT</i>	<i>MOUNTAIN V</i>

