



49 CFR 192.473 External Corrosion Control: Interference Currents

- (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
- (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 11-6-13	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 1311106
------------------------	--	-------------------------------

General Data

Company EQT Midstream	Contact Joe Paulay	
Address PO Box 1550 Clarksburg, WV 26301	Office Phone	Cell Phone 304-266-9175

Rectifier/Ground Bed Location

At Cabin Run across from the mouth of Gum Run,

County Doddridge	Tax District
Nearest Town or Municipality Toll Gate	Property Owner

Rectifier Data

Rectifier Designation / Description

J.A.

Rated Output 40 DC Volts	Operating Output 11.04 DC Volts	Date Output Taken Nov. 4, 2013
20 DC Amps	4.30 DC Amps	

Ground Bed Description

Location From Rectifier

300 Feet ☐ North ☐ Northeast ☐ East ☐ Southeast ☐ South ☐ Southwest ☒ West ☐ Northwest

Type of Ground Bed Point	Number of Anodes	Type of Anodes MMO	Anode Spacing Feet
------------------------------------	------------------	------------------------------	-----------------------

Structure Protected

Type of Structure Pipeline	Size 12"	Length 8.2 miles
Coating Type FBE	Remarks	

Other Structures

Companies that may be Affected Key Oil	Dominion	Eastern American