

**49 CFR 192.473 External Corrosion Control: Interference Currents**

- (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
- (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 11-6-13	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 1311107
------------------------	--	-------------------------------

General Data

Company EQT Midstream	Contact Bill King
Address PO Box 1550 Clarksburg, WV 26301	Office Phone Cell Phone 304-266-7197

Rectifier/Ground Bed Location

Blacksville Compressor Station, Off Rt. 7,

County Monongalia	Tax District
Nearest Town or Municipality Blacksville	Property Owner

Rectifier Data

Rectifier Designation / Description JA		
Rated Output 40 DC Volts 20 DC Amps	Operating Output 39 DC Volts 12 DC Amps	Date Output Taken 11-5-13

Ground Bed Description

Location From Rectifier Feet <input type="checkbox"/> North <input type="checkbox"/> Northeast <input type="checkbox"/> East <input type="checkbox"/> Southeast <input type="checkbox"/> South <input type="checkbox"/> Southwest <input type="checkbox"/> West <input type="checkbox"/> Northwest			
Type of Ground Bed Distributor	Number of Anodes	Type of Anodes MMO	Anode Spacing Feet

Structure Protected

Type of Structure Comp. Sta. Piping	Size	Length
Coating Type FBE	Remarks	

Other Structures

Companies that may be Affected Northeast Energy	