

		49 CFR 192.473 External Corrosion Control: Interference Currents (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents. (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.	
Rectifier Directory			
Date	9/12/2011	Location Map Attached	Case Number
		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	1109108
General Data			
Company		Contact	
EQT Midstream		Joe Pauley	
Address		Office Phone	Cell Phone
PO Box 1550 Clarksburg, WV 26301		304-627-6437	304-266-9175
Rectifier/Ground Bed Location			
Off Central Station Road from RT 50 near West Union WV.			
County		Tax District	
Doddridge			
Nearest Town or Municipality		Property Owner	
West Union		EQT Midstream	
Rectifier Data			
Rectifier Designation / Description			
JA Single Phase			
Rated Output		Operating Output	
40	DC Volts	11.03	DC Volts
20	DC Amps	5.4	DC Amps
			Date Output Taken
			9/1/11
Ground Bed Description			
Location From Rectifier			
50-300	Feet	<input checked="" type="checkbox"/> North <input type="checkbox"/> Northeast <input type="checkbox"/> East <input type="checkbox"/> Southeast <input type="checkbox"/> South <input type="checkbox"/> Southwest <input type="checkbox"/> West <input type="checkbox"/> Northwest	
Type of Ground Bed	Number of Anodes	Type of Anodes	Anode Spacing
Distributed		MMO	Feet
Structure Protected			
Type of Structure		Size	Length
Compressor Station Piping		2"-16"	
Coating Type	Remarks		
FBE			
Other Structures			
Companies that may be Affected		Equitable Gas Company	