



49 CFR 192.473 External Corrosion Control: Interference Currents
 (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
 (b) Each impressed current type cathodic protection system or galvanic anodic system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 4-13-09	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 0904104
------------------------	--	-------------------------------

General Data

Company EQT Midstream	Contact Joe Pauley
Address PO Box 1550 Clarksburg, WV 26301	Office Phone 1-304-627-6437
	Cell Phone 1-304-266-9175

Rectifier/Ground Bed Location**Macdale WV just off RT 7**

County Monongahelia	Tax District
Nearest Town or Municipality Macdale	Property Owner

Rectifier Data**Rectifier Designation / Description****JA**

Rated Output	Operating Output	Date Output Taken
DC Volts	23.1	4-13-09
DC Amps	4.06	

Ground Bed Description**Location From Rectifier**
 Feet ☐ North ☐ Northeast ☐ East ☐ Southeast ☐ South ☐ Southwest ☐ West ☐ Northwest

Type of Ground Bed	Number of Anodes	Type of Anodes	Anode Spacing
			Feet

Structure Protected

Type of Structure FBE Coated steel pipe	Size 12"	Length 10 miles
Coating Type FBE AND Coal Tar	Remarks I just increased the output of this rectifier from 4/6 to 6/6.	

Other Structures

Companies that may be Affected	Dominion	Dominion Hope
Equitable Gas	East Resources	Waco