



49 CFR 192.473 External Corrosion Control: Interference Currents

(a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.

(b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 1/15/2009	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 100/100
-------------------	--	------------------------

General Data

Company Mountaineer Gas Company	Contact Tate Withrow
Address 1205 6th Ave Huntington, WV 25701	Office Phone 304-528-2525
	Cell Phone 304-360-0599

Rectifier/Ground Bed Location 680 Main St. Ceredo, WV
--

County Wayne	Tax District
Nearest Town or Municipality Ceredo	Property Owner

Rectifier Data

Rectifier Designation / Description GoodALL			
Rated Output 18	DC Volts	Operating Output 12	DC Volts
42	DC Amps	9	DC Amps
Date Output Taken 12/22/2009			

Ground Bed Description

Location From Rectifier 100 Feet		<input type="checkbox"/> North <input type="checkbox"/> Northeast <input type="checkbox"/> East <input type="checkbox"/> Southeast <input type="checkbox"/> South <input type="checkbox"/> Southwest <input type="checkbox"/> West <input checked="" type="checkbox"/> Northwest					
Type of Ground Bed Conventional	Number of Anodes 4	Type of Anodes Mixed Metal Oxide		Anode Spacing Feet			

Structure Protected

Type of Structure Pipeline	Size 12	Length 12800
Coating Type Coal Tar	Remarks	

Other Structures

Companies that may be Affected		