



49 CFR 192.473 External Corrosion Control: Interference Currents
 (a) Each operator whose pipeline system is subject to stray currents shall have in effect a continuing program to minimize the detrimental effects of such currents.
 (b) Each impressed current type cathodic protection system or galvanic anode system must be designed and installed so as to minimize any adverse effects on existing adjacent underground metallic structures.

Rectifier Directory

Date 9-21-10	Location Map Attached <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Case Number 10/0102
-----------------	--	------------------------

General Data

Company Dominion Transmission	Contact Gloria A. Dennison
Address HC 69 BOX 11 WEST UNION, WV 26456	Office Phone (304)269-4901 Ext. 5324
	Cell Phone (304)266-5951

Rectifier/Ground Bed Location

MAXWELL COMPRESSOR STATION

County DODDRIDGE	Tax District
Nearest Town or Municipality MARKET	Property Owner Dominion Transmission

Rectifier Data

Rectifier Designation / Description

Rated Output 30 DC Volts	Operating Output 22.2 DC Volts	Date Output Taken 9-21-10
15 DC Amps	6.75 DC Amps	

Ground Bed Description

Location From Rectifier Feet <input type="checkbox"/> North <input type="checkbox"/> Northeast <input type="checkbox"/> East <input type="checkbox"/> Southeast <input type="checkbox"/> South <input type="checkbox"/> Southwest <input type="checkbox"/> West <input type="checkbox"/> Northwest			
Type of Ground Bed Conventional	Number of Anodes 9	Type of Anodes Mix Metal Oxide	Anode Spacing 70 Feet

Structure Protected

Type of Structure STATION	Size	Length
Coating Type	Remarks	

Other Structures

Companies that may be Affected	P & G SALEM